Application No.: 09/966,825 Case No.: 54605US002

Siver

(a) forming a contoured polymeric dielectric film layer;

- (b) joining the contoured film layer to a second layer at at least one face of the contoured film layer so as to stabilize the contoured film layer and form flow channels and form a flow channel layer assembly; and
- (c) electrostaticly charging the flow channel layer assembly of the contoured film layer and the second layer with an electret charge to form a charged filtration media array.

34. 35 (TWICE AMENDED) The method of forming a filtration media array of claim 35 further comprising layering multiple charged filtration media arrays formed by steps (a) - (c) so as to create a filter having multiple flow channel layers.

35. 34 (ONCE AMENDED) The method of forming a filtration media array of claim 34 33 further comprising joining the adjacent flow channel layers by partially melting at least one face of the multilayer flow channel assembly.

36. 3 (TWICE AMENDED) A method of forming a filtration media array comprising the steps of:

- (a) forming a contoured polymeric film layer;
- (b) joining the contoured film layer to a second layer at least one face of the contoured film layer so as to stabilize the contoured film layer and form a series of adjacent flow channels and form a flow channel layer assembly;
- (c) layering the flow channel layer assembly so as to create a filtration media array having multiple flow channel layers forming fluid pathways through the filtration media array; and
- (d) slicing the filtration media array with a hot wire so as to fuse the adjacent layers forming the filtration media array and directly form a dimensionally stable three dimensional filter media.

13

37. The method of forming a filtration media array of claim of further comprising separating a portion of the filtration media array sliced by the hot wire.

A version marked up to show changes made to the claim(s) relative to the previous version of the claim(s) is attached.